

## MAX Pro Specifications

<p><b>Maximum Engraving Area:</b></p> <p><b>Max. Workpiece Clearance:</b></p> <p><b>Table Overall Dimensions:</b></p> <p><b>Controller Dimensions:</b></p> <p><b>Standard Spindle:</b></p> <p><b>Spindle Options:</b></p> <p><b>Spindle Clearance:</b></p> <p><b>Z-Axis Stroke:</b></p> <p><b>Standard Features:</b></p> <p><b>Available Options:</b></p>  <p><b>Software:</b></p> <p><b>Control Display Panel:</b></p> <p><b>Motion Control:</b></p> <p><b>Resolution:</b></p> <p><b>Speed/Spindle RPM Control:</b></p> <p><b>Computer Interface:</b></p> <p><b>3-D Capabilities:</b></p> <p><b>Electrical Requirements:</b></p> <p><b>Max. Ambient Temperature:</b></p> <p><b>Warranty:</b></p> <p><b>Shipping Information:</b></p>	<p>8" x 12"</p> <p>Flat = 14" x Any Width x 3"      Cylindrical = 12" x 6" diameter</p> <p>28" x 28" x 26"</p> <p>Built - In</p> <p>1 1/64" or 1/4" Top Loading</p> <p>Top/Bottom collet</p> <p>Cylindrical/Flat = 3"      With Vise = 7"</p> <p>3"</p> <p>Relocatable Home Position &amp; Center Engraving Option</p> <p>Self Centering Vise &amp; 8" x 12" T-Slot Table</p> <p>Surface Sensor for automatically setting down position</p> <p>Integratged water cooling system for glass engraving</p> <p>Adjustable Edge Guides (Imperial or Metric Markings)</p> <p>Quick Lock Vise</p> <p>Hand-Held Pendant</p> <p>Red Laser Pointer for easy set-ups</p> <p>Cones for holding cylindrical items</p> <p>Inside/Outside Ring Attachment</p> <p>Multi Mat work holding mat</p> <p>Diamond Drag Adapter</p> <p>Carbide Engraving Cutters</p> <p>Diamond Burnishers &amp; Burnishing Adapters</p> <p>Vacuum Chip Removal System</p> <p>Versa Vise</p> <p>Table Tape and Dispenser</p> <p>Workholding Jigs and Clamps</p> <p>Vision Windows or Vision Pro, drivers for 3rd Party Software</p> <p>LCD on Pendant with digital display of Position, Feeds, Job Time</p> <p>Independent Microstepping Drives and Motors for each axis (X,Y,Z &amp; R)</p> <p>.0002"</p> <p>Control of all speeds from software and/or front panel</p> <p>Ethernet (recommended) or Serial (RS232 - 9 pin port)</p> <p>2 1/2D and 3D capable with additional software</p> <p>110/220V, 50/60Hz 10 amp</p> <p>32°C (90°F) Maximum Ambient Room Temperature</p> <p>Two year factory warranty. Up to Three additional years available.</p> <p>35" x 39" x 37" 353lbs</p>
--	---